

# ATLANTA FR

## Honeycomb Fabric Specification

### KEY FEATURES

Fabric composition:	100% Polyester
Fire retardancy:	Tested to DIN 4102 norm and compliant with the European B1 standard
Shading:	Semi-transparent recommended for computer environments
Moisture resistance:	Suitable for moist conditions

### STANDARD SPECIFICATIONS

Colour range:	8
Pleated cell width:	25mm
Fabric width:	300cm
Fabric weight:	300 g/m <sup>2</sup>
Fabric thickness:	0.23mm
Care instructions:	Soak in 30°C water with mild detergent. Rinse well and hang closed to dry. Raise and lower the blind several times to prevent cells sticking together.

Colour	Lf	Rv	Av	Tv	Rs	As	Ts	Tuv	Gtot	Fc Value	Fc Class
White	4-5	49%	18%	33%	46%	14%	40%	17%	0.47	0.66	3
Beige	4-5	47%	17%	36%	48%	12%	40%	18%	0.46	0.65	3
Grey	4-5	41%	32%	27%	47%	20%	33%	14%	0.46	0.65	3
Pebble	4-5	58%	15%	27%	57%	12%	31%	8%	0.39	0.66	3
Smoke	4-5	53%	38%	9%	52%	35%	13%	4%	0.40	0.68	3
Dust	4-5	57%	23%	20%	57%	16%	27%	7%	0.39	0.65	3
Fossil	4-5	56%	19%	25%	56%	16%	28%	7%	0.39	0.66	3
Mercury	4-5	48%	24%	28%	47%	21%	32%	13%	0.46	0.65	3

**Lf** = Lightfastness : **Rv** = Light reflection : **Av** = Light absorption : **Tv** = Light transmittance % : **Rs** = Solar reflectance % : **As** = Solar absorptance % : **Ts** = Solar transmittance % : **Tuv** = UV transmittance % : **Gtot** = Gtot value