

HIVE BLACKOUT FR

Honeycomb Fabric Specification

KEY FEATURES

Fabric composition:	100% polyester
Fire retardancy:	BS5867 – 2, Type B; 2008 for fire retardancy when tested in accordance with BS EN USI 15025-2002 (A-Surface) European Standard – B1 Din 4102
Shading:	Blackout + reflective backing - recommended for computer environments
Moisture resistance:	Suitable for moist conditions

STANDARD SPECIFICATIONS

Colour range:	5
Pleated cell width:	25mm
Fabric width:	225cm
Fabric weight:	330 g/m ²
Fabric thickness:	0.15mm
Colourfast:	Conforms to; BS5867 - 1 : 2004 for light fastness to Grade 6 minimum when tested in accordance with ISO 105 - B02 : 1999
Care instructions:	Wipe with damp sponge

Colour	%Heat		%Light		S-C
	T	R	T	R	
Concrete	0	72	0	77	0.24
Iron	0	72	0	77	0.24
Sand	0	72	0	77	0.24
White	0	72	0	77	0.24
Cream	0	72	0	77	0.24

T = Transmitted : R = Reflected : S-C = Shading Co-efficient. Shading Co-efficients are expressed as a decimal between 0 and 1. The lower the figure, the higher the shading efficiency of the blind.

All data is based on; Tests conducted using double glazed 6mm float glass with 12mm air space. Blinds are fully closed. Shading co-efficients are calculated for radiation at normal incidence. Standard U value is 2.75 W/M2K = 0.49Btu/ft2hx°F.

Important: Performance data has been compiled with great care using the latest techniques. However, it is advisable to check actual suitability of fabrics for a particular application before use. In line with Hunter Douglas's commitment to product development, specifications may be subject to change without notice.