

SEATEX™

Roller Blind Fabric Specification

KEY FEATURES

Fabric composition:	50% Polyester 50% reclaimed ocean plastic
Fire retardancy:	M2
Shading:	Semi- Transparent Screen - Suitable for computer environments
Moisture resistance:	Suitable for moist conditions

STANDARD SPECIFICATIONS

Colour range:	5
Roller fabric width:	300cm (118.1") nominal
Typical fabric weight:	250gsm - (+/-10)
Fabric thickness:	0.45mm - nominal
Colourfast:	Conforms to: BS5867 - 1 : 2004 for light fastness to Grade 6 minimum when tested in accordance with ISO 105 - B02 : 1999
Care instructions:	Brush Clean

Colour	%Heat		%Light		S-C
	T	R	T	R	
Graphite	19	31	5	9	0.63
Haze	26	52	19	45	0.45
Pearl	23	47	13	34	0.49
Sand	26	55	22	53	0.43
White	31	59	31	62	0.40

T = Transmitted : **R** = Reflected : **S-C** = Shading Co-efficient. Shading Co-efficients are expressed as a decimal between 0 and 1. The lower the figure, the higher the shading efficiency of the blind.

This data is based on: Tests conducted using double glazed 6mm float glass with 12mm air space. Blinds are fully closed. Shading co-efficients are calculated for radiation at normal incidence. Standard U value is 2.75 W/M2K = 0.49Btu/ft2hxF

Important: Performance data has been compiled with great care using the latest techniques.

However, it is advisable to check actual suitability of fabrics for a particular application before use.

In line with Hunter Douglas's commitment to product development, specifications may be subject to change