

BOUCLE

Vertical & Roller Blind Fabric Specification

KEY FEATURES

Fabric composition:	71% PVC, 29% Fiberglass
Fire retardancy:	Conforms to; BS5867 - 2, Type B : 2008 for fire retardancy when tested in accordance with BS5438 : 1989
Shading:	Block-out - Suitable for computer environments
Moisture resistance:	Suitable for moist conditions

STANDARD SPECIFICATION

Colour range:	5
Louvre widths available:	89mm (3 ^{1/2} ")
Roller fabric width:	180cm - (78"): nominal
Typical fabric weight:	390gsm - (+/-10)
Fabric thickness:	0.30mm – nominal
Colourfast:	Conforms to: BS5867 - 1 : 2004 for light fastness to Grade 6 minimum when tested in accordance with ISO 105 - B02 : 1999
Care instructions:	Wipe with damp sponge; Do not wash, tumble dry, dry clean or iron

Colour	%Heat		%Light		S-C
	T	R	T	R	
Champagne	0	62	0	61	0.33
Black	0	6	0	6	0.82
White	0	72	0	88	0.24
Dark Grey	0	12	0	12	0.77
Light Grey	0	46	0	48	0.47

T = Transmitted : R = Reflected : S-C = Shading Co-efficient. Shading Co-efficients are expressed as a decimal between 0 and 1. The lower the figure, the higher the shading efficiency of the blind.

This data is based on: Tests conducted using double glazed 6mm float glass with 12mm air space. Blinds are fully closed. Shading co-efficients are calculated for radiation at normal incidence. Standard U value is 2.75 W/M2K = 0.49Btu/ft2hx°F.

Important: Performance data has been compiled with great care using the latest techniques However it is advisable to check actual suitability of fabrics for a particular application before use. In line with Hunter Douglas's commitment to product development, specifications may be subject to change without notice

